Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2007	7DZXL01.6050	1.17, 1.56	Diesel	5000
	FEATURES & EMISSION		TYPICAL EQUIPMENT APPLK	
	Indirect Diesel Inje	ction	Crane, Loader, Tractor, Pump, C	Compressor

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION			E	XHAUST (g/kW-l	nr)		O	PACITY (%	6)
POWER CLASS	STANDARD CATEGORY		HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
8 ≤ kW < 19	Tier 2	STD	N/A	N/A	7.5	6.6	0.80	20	15	50
19 < kW < 37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	20	15	50
		CERT	-	-	5.6	0.7	0.20	4	3	6

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this _____2624___ day of December 2006.

Annette Hebert, Chief

Rophael Susnowith

Mobile Source Operations Division

Engine Model Summary Form

Manufacturer: Deutz AG

Engine category: Nonroad Cl

EPA Engine Family: 70220.01.0050

Mfr Farrily Name: D2006L03, D2006L04

Process Code: New Submission

Attachment E0#4-2-013-0211

D2008L03 25,7@3000 D2008L03 24,4@2800 D2008L03 22,2@2500 D2008L04 34,5@3000 D2008L04 32,4@2800 D2008L04 30,7@2600 D2008L04 29,5@2500 D2008L04 28,8@2400	I. Engine Code	2. Engine Model	3.BHP@RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for desal only)	5. Fuel Rate: (Ibs/hr) @ peak HP (for desets only)	6.Torque @ RPM (SEA Gross)	7.Fuel Pate: mm/stroke@paak torque	8.Fuel Rate: (lbs/hr)@peak torque I	9. Emission Control Device Per SAE J1830
D2008L03 24,4@2800 20,9 9,7 52,5@2000 23,4 7,7 D2008L03 22,2@2500 21 8,7 52,5@2000 23,4 7,7 D2008L04 34,5@3000 21,5 14,3 70,3@2000 23,7 10,5 D2008L04 32,4@2800 20,9 13 70,3@2000 23,7 10,5 D2008L04 39,5@2500 21,4 11,8 70,3@2000 23,7 10,5 D2008L04 29,5@2500 21,4 11,8 70,3@2000 23,7 10,5 D2008L04 29,5@2500 21,4 11,8 70,3@2000 23,7 10,5 D2008L04 28,8@2400 21,4 11,4 70,3@2000 23,7 10,5 D2008L03 21,4@2400 21,1 8,4 52,5@2000 23,7 10,5	3019.2	D2008L03	25,7@3000	212	10,5	52,5@2000	23,4	7,7	Δ
D2008L03 23@2600 20,9 9 52,5@2000 23,4 7,7 D2008L03 22,2@2500 21 8,7 52,5@2000 23,4 7,7 D2008L04 34,5@3000 21,5 14,3 70,3@2000 23,7 10,5 D2008L04 30,7@2600 21,4 12,3 70,3@2000 23,7 10,5 D2008L04 29,5@2500 21,4 11,8 70,3@2000 23,7 10,5 D2008L04 29,5@2500 21,4 11,4 70,3@2000 23,7 10,5 D2008L04 28,6@2400 21,4 11,4 70,3@2000 23,7 10,5 D2008L03 21,4@2400 21,1 8,4 52,5@2000 23,4 7,7	O118.2	D2008L03	24.4@2800	20,9	9,7	52,5@2000	23,4	7,7	
D2008L03 22,2@2500 21,5 8,7 52,5@2000 23,4 7,7 D2008L04 34,5@3000 21,5 14,3 70,3@2000 23,7 10,5 D2008L04 32,4@2800 21,4 12,3 70,3@2000 23,7 10,5 D2008L04 39,5@2500 21,4 11,8 70,3@2000 23,7 10,5 D2008L04 28,8@2400 21,4 11,4 70,3@2000 23,7 10,5 D2008L03 21,4@2400 21,1 8,4 52,5@2000 23,4 7,7	O17.2	D2008L03	23@2600	20,9	6	52,5@2000	23,4	7,7	Ω
D2008L04 34,5@3000 21,5 14,3 70,3@2000 23,7 10,5 D2008L04 32,4@2800 20,9 13 70,3@2000 23,7 10,5 D2008L04 30,7@2600 21,4 11,8 70,3@2000 23,7 10,5 D2008L04 29,5@2500 21,4 11,8 70,3@2000 23,7 10,5 D2008L04 28,8@2400 21,4 11,4 70,3@2000 23,7 10,5 D2008L03 21,4@2400 21,1 8,4 52,5@2000 23,4 7,7	016.6	D2008L03	22.2@2500	2	8,7	52,5@2000	23,4	7,7	
D2008L04 32,4@2800 20,9 13 70,3@2000 23,7 10,5 D2008L04 30,7@2500 21,4 11,8 70,3@2000 23,7 10,5 D2008L04 29,5@2500 21,4 11,4 70,3@2000 23,7 10,5 D2008L04 28,8@2400 21,4 11,4 70,3@2000 23,7 10,5 D2008L03 21,4@2400 21,1 8,4 52,5@2000 23,7 7,7	0125.8	D2008L04	34,5@3000	21,5	14,3	70,3@2000	23,7	10,5	
D2008L04 30,7@2600 21,4 12,3 70,3@2000 23,7 10,5 D2008L04 29,5@2500 21,4 11,8 70,3@2000 23,7 10,5 D2008L04 28,8@2400 21,4 11,4 70,3@2000 23,7 10,5 D2008L03 21,4@2400 21,1 8,4 52,5@2000 23,4 7,7	0 24.2	D2008L04	32,4@2800	20,9	13	70,3@2000	7,83	10,5	۵
D2008L04 29,5@2500 21,4 11,8 70,3@2000 23,7 D2008L04 28,8@2400 21,4 70,3@2000 23,7 D2008L03 21,4@2400 21,1 8,4 52,5@2000 23,4	0 22 9	D2008L04	30,7@2600	21,4	12,3	70,3@2000	7,82	10,5	
D2008L04 28,8@2400 21,4 70,3@2000 23,7 D2008L03 21,4@2400 21,1 8,4 52,5@2000 23,4	30 22	D2008L04	29,5@2500	21,4	11,8	70,3@2000	7,83	10,5	
D2008L03 21,4@2400 21,1 8,4 52,5@2000 23,4	OI21,5	D2008L04	28,8@2400	21,4	7.1	70,3@2000	23,7	10,5	٥
	30116	D2008L03	21.4@2400	21,1	8,4	52,5@2000	23,4	7'2	<u></u>