DEUTZ AG

EXECUTIVE ORDER U-R-013-0399 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2011	BDZXL06.1077	6.057	Diesel	8000
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT	APPLICATION
Char	ectronic Direct Injection, 1 ge Air Cooler, Electronic e Puff Limiter, Exhaust G	Control Module,	Tractor, Other Industri	al Equipment

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD			E	EXHAUST (g/kw-l	1 ୮)		OF	ACITY (%	5)
CLASS	CATEGORY		нс	NOx	NMHC+NOx	0	PM	ACCEL	LUG	PEAK
75 ≤ kW < 130	Tier 3	STD	N/A	N/A	4.0	5.0	0.30	20	15	50
		CERT			3.8	0.9	0.12	14	7	30

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

_

Annette Hebert, Chief

Mobile Source Operations Division

day of April 2011.

Ahweart page	Doutz AG			Enç	Engine Model	Model Summary Template	<u>Template</u>		£0#	E0# 0-R-013-0399	
4.Fuel Rate: T.Fuel Rate: A.Fuel Rate: <th colspan<="" th=""><th>Y-</th><th></th><th></th><th>Attac</th><th>hment</th><th>dod</th><th>-</th><th></th><th>4/10</th><th>110<!--</th--></th></th>	<th>Y-</th> <th></th> <th></th> <th>Attac</th> <th>hment</th> <th>dod</th> <th>-</th> <th></th> <th>4/10</th> <th>110<!--</th--></th>	Y -			Attac	hment	dod	-		4/10	110 </th
85 59.4 543.5@1450 107 51.7 76 53.1 481.6@1450 95 45.9 67 46.8 402.7@1450 84,5 40.8 1 87 60.8 511.2@1600 105 55.9 1 88.5 61.9 528.8@1600 102.5 54.6 1 83.5 58.4 446.9@1600 87 46.3 1 82.5 47.9 429.9@1600 88.5 42.7 1 74.5 52.1 441.6@1400 90. 41.9 1 87.5 61.2 549.3@1450 106 51.2 1	ハりかから でん しよ 3.BHP@RPM Engine Family 1.Engine Code 2.Engine Model (SAE Gross)		3.BHP@		4.Fuel Rate: nm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM ™ (SEA Gross)		8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930	
76 53.1 481.6@1450 95 45.9 67 46.8 402.7@1450 84,5 40.8 1 87 60.8 511.2@1600 105 55.9 1 88.5 61.9 528.8@1600 102.5 54.6 1 68.5 47.9 446.9@1600 87 46.3 1 82.5 57.7 485.8@1400 95.5 44.5 1 74.5 52.1 441.6@1400 90 41.9 1 87.5 61.2 549.3@1450 106 51.2 1	C3CT123 TCD2012L06 164.9		164.9	164.9@2100	85	59.4	543.5@1450	107	51.7	DDI, TC, CAC, ECM, SPL,	
67 46.8 402.7@1450 84,5 40.8 87 60.8 511.2@1600 105 55.9 88.5 61.9 528.8@1600 102.5 54.6 83.5 58.4 446.9@1600 87 46.3 68.5 47.9 429.9@1600 88.5 42.7 82.5 57.7 485.8@1400 96.5 44.5 74.5 52.1 441.6@1400 90 41.9 87.5 61.2 549.3@1450 106 51.2	C3CT108 TCD2012L06 144.8		144.8	144.8@2100	76	53.1	481.6@1450	95	45.9	DDI, TC, CAC, ECM, SPL	
87 60.8 511.2@1600 105 55.9 88.5 61.9 528.8@1600 102.5 54.6 83.5 58.4 446.9@1600 87 46.3 68.5 47.9 429.9@1600 88.5 42.7 82.5 57.7 485.8@1400 95.5 44.5 74.5 52.1 441.6@1400 90 41.9 87.5 61.2 549.3@1450 106 51.2	C3CT93 TCD2012L06 124.7@		124.7@	32100	67	46.8	402.7@1450	84,5	40.8	DDI, TC, CAC, ECM, SPL,	
88.5 61.9 528.8@1600 102.5 54.6 83.5 58.4 446.9@1600 87 46.3 68.5 47.9 429.9@1600 88.5 42.7 82.5 57.7 485.8@1400 95.5 44.5 74.5 52.1 441.6@1400 90 41.9 87.5 61.2 549.3@1450 106 51.2	C3CT124 TCD2012L06 166.6	ļ	166.6	92100	87	60.8	511.2@1600	105	55,9	DDI, TC, CAC, ECM, SPL,	
83.5 58.4 446.9@1600 87 46.3 68.5 47.9 429.9@1600 88.5 42.7 82.5 57.7 485.8@1400 96.5 44.5 74.5 52.1 441.6@1400 90 41.9 87.5 61.2 549.3@1450 106 51.2	C3CT129 TCD2012L06 173.3@		173.3(32100	88.5	61.9	528.8@1600	102.5	54.6	DDI, TC, CAC, ECM, SPL,	
68.5 47.9 429.9@1600 88.5 42.7 82.5 57.7 485.8@1400 95.5 44.5 74.5 52.1 441.6@1400 90 41.9 87.5 61.2 549.3@1450 106 51.2	C3CT121 TCD2012L06 162.5(162.5(<u> 3</u> 2100	83.5	58.4	446.9@1600	87	46.3	DDI, TC, CAC, ECM, SPL,	
82.5 57.7 485.8@1400 95.5 44.5 74.5 52.1 441.6@1400 90 41.9 87.5 61.2 549.3@1450 106 51.2	C3CT97 TCD2012L06 130@	 	130@	02100	68.5	47.9	429.9@1600	88.5	42.7	DDI, TC, CAC, ECM, SPL,	
74.5 52.1 441.6@1400 90 41.9 87.5 61.2 549.3@1450 106 51.2	C3CT120 TCD2012L06 160.6		160.6	@2100	82.5	57.7	485.8@1400	95.5	44.5	DDI, TC, CAC, ECM, SPL,	
87.5 61.2 549.3@1450 106 51.2	C3CT107 TCD2012L06 142.9		142.9	@2100	74.5	52.1	441.6@1400	90	41.9	DDI, TC, CAC, ECM, SPL,	
	C3CT129A TCD2012L06 173.3		173.3	173.3@2100	87.5	61.2	549.3@1450	106	51.2	DDI, TC, CAC, ECM, SPL, V	