

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapters 1 and 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

**IT IS ORDERED AND RESOLVED:** The engines and emission control systems produced by the manufacturer as described below are certified for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

Model Year	Engine Family	Combustion Cycle	Fuel Operation	Fuel Type(s)	Engine Operation
2024	RDZXL02.9020	Diesel	Dedicated	Diesel	Variable and Constant Speed

Emission Control Systems	Special Features
[1]: Direct Diesel Injection (DDI), Turbocharger (TC), Electronic Control Module (ECM), Exhaust Gas Recirculation (EGR), Diesel Oxidation Catalyst (DOC)	None

The certified engine models are attached.

The listed engine models comply with the following: 1) emission standard limits (STD) and Not-To-Exceed (NTE) limits, as applicable, for criteria pollutants non-methane hydrocarbon plus oxides of nitrogen (NMHC+NO<sub>x</sub>), carbon monoxide (CO), and particulate matter (PM), and for smoke opacity as demonstrated during the Acceleration (ACL) and Lugging (LUG) modes, and the peak value (PEAK) in either mode of the Smoke Opacity cycle, as set forth in 13 CCR 2423 and the applicable California test procedures for off-road compression-ignition engines, and 2) family emission limits (FEL) declared by the manufacturer as allowed by the applicable California test procedures, stated in units of gram per kilowatt-hour (g/kWh-hr) and percent opacity (%opacity), respectively, except as noted, or designated as not applicable (\*).

Applicable Standard		Criteria			Smoke Opacity		
		NMHC+NO <sub>x</sub>	CO	PM	ACL	LUG	PEAK
Tier 4 Final 37 ≤ kW < 56	STD	4.7	5.0	0.03	*	*	*
	FEL	*	*	*	*	*	*
	NTE	5.9	6.2	0.04	*	*	*

**BE IT FURTHER RESOLVED:** Any declared FEL is the emission limit to which all engines must comply in lieu of the standard limit for certification purposes, subject to the restrictions of averaging, banking, or trading (ABT) programs allowed by the applicable California test procedures.

**BE IT FURTHER RESOLVED:** For the listed engine models, the manufacturer has submitted materials to demonstrate certification compliance with 13 CCR 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control warranty).

**BE IT FURTHER RESOLVED:** The listed engine models may only be installed in or on equipment such that engine operation is consistent with off-road compression-ignition engines as defined in 13 CCR 2421(a)(39).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this 16th day of August 2023.



Robin U. Lang, Chief  
 Emissions Certification and Compliance Division

**ATTACHMENT: ENGINE MODELS**

Family: RDZXL02.9020 EO Number: U-R-013-0714 Date Applicable: 7/16/2024

Model	Code	Trim	Config	Displacement	Peak Power			Peak Torque			ECS Num	GHG	Notes
					Power	Speed	Fueling	Torque	Speed	Fueling			
-	-	-	-	L	hp	rpm	lb/hr	lb-ft	rpm	lb/hr	-	-	-
TD2.9L4	C4DI55C		L4	2.925	74.2	2300	29.7	191.7	1800	24.9	1	N/A	
TD2.9L4	C4DI49A		L4	2.925	65.7	2200	26.3	172.5	1800	22.4	1	N/A	
TD2.9L4	C4DI45D		L4	2.925	60.3	2600	29.4	172.5	1800	22.4	1	N/A	
TD2.9L4	C4DI45E		L4	2.925	60.3	2500	26.6	172.5	1800	22.4	1	N/A	
TD2.9L4	C4DI50E		L4	2.925	67	2500	28.8	172.5	1800	22.4	1	N/A	
TD2.9L4	C4DI49J		L4	2.925	65.7	2200	26.3	172.5	1800	22.4	1	N/A	New code
TD2.9L4	C4DI45		L4	2.925	60.3	2600	29.4	172.5	1800	22.4	1	N/A	
TD2.9L4	C4DI36EU		L4	2.925	48.8	2200	20.5	183.6	1350	18.4	1	N/A	
TD2.9L4	C4DI50G		L4	2.925	67	2300	27.5	172.5	1800	22.4	1	N/A	
TD2.9L4	C4DI55F		L4	2.925	74.2	2400	30.3	191.7	1800	24.9	1	N/A	
TD2.9L4	C4DI55D		L4	2.925	74.2	2600	32.4	191.7	1800	24.9	1	N/A	
TD2.9L4	C4DI50D		L4	2.925	67	2600	30.9	172.5	1800	22.4	1	N/A	
TD2.9L4	C4DI54A		L4	2.925	72.4	2200	28.3	191.7	1800	24.9	1	N/A	
TD2.9L4	C4DI55E		L4	2.925	74.2	2500	31.4	191.7	1800	24.9	1	N/A	
TD2.9L4	C4DI55K		L4	2.925	74.2	2600	32.4	191.7	1800	24.9	1	N/A	
TD2.9L4	C4DI55G		L4	2.925	74.2	2300	29.7	191.7	1800	24.9	1	N/A	
TD2.9L4	C4DI55,4		L4	2.925	74.2	2600	32.4	191.7	1800	24.9	1	N/A	
TD2.9L4	C4DI50C		L4	2.925	67	2300	27.5	172.5	1800	22.4	1	N/A	
TD2.9L4	C4DI55A		L4	2.925	74.2	2500	31.4	191.7	1800	24.9	1	N/A	
TD2.9L4	C4DI45A		L4	2.925	60.3	2500	26.6	172.5	1800	22.4	1	N/A	
TD2.9L4	C4DT50		L4	2.925	67	2200	26.6	191.7	1800	21.5	1	N/A	
TD2.9L4	C4DI45B		L4	2.925	60.3	2200	24.7	172.5	1800	22.4	1	N/A	
TD2.9L4	C4DT45		L4	2.925	60.3	2200	24.1	179.9	1800	22.7	1	N/A	
TD2.9L4	C4DI54		L4	2.925	72.4	2200	28.3	191.7	1800	24.9	1	N/A	
TD2.9L4	C4DI49		L4	2.925	65.7	2200	26.3	172.5	1800	22.4	1	N/A	
TD2.9L4	C4DI45F		L4	2.925	60.3	2200	24.7	172.5	1800	22.4	1	N/A	
TD2.9L4	C4DI55B		L4	2.925	74.2	2400	30.3	191.7	1800	24.9	1	N/A	
TD2.9L4	C4DI50		L4	2.925	67	2600	30.9	172.5	1800	22.4	1	N/A	
TD2.9L4	C4DT54		L4	2.925	72.4	2200	28.5	191.7	1800	21.6	1	N/A	
TD2.9L4	C4DI50A		L4	2.925	67	2500	28.8	172.5	1800	22.4	1	N/A	