

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapters 1 and 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

**IT IS ORDERED AND RESOLVED:** The engines and emission control systems produced by the manufacturer as described below are certified for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

Model Year	Engine Family	Combustion Cycle	Fuel Operation	Fuel Type(s)	Engine Operation
2025	SDZXL06.1059	Diesel	Dedicated	Diesel	Variable-speed and Constant-speed

Emission Control Systems	Special Features
[1]: Direct Diesel Injection (DDI), Turbocharger (TC), Charge Air Cooler (CAC), Electronic Control Module (ECM), Exhaust Gas Recirculation (EGR), Diesel Oxidation Catalyst (DOC), Continuous Trap Oxidizer (CTOX), Selective Catalytic Reduction-Urea (SCR-U), Ammonia Oxidation Catalyst (AMOX)	None

The certified engine models are attached.

The listed engine models comply with the following: 1) emission standard limits (STD) and Not-To-Exceed (NTE) limits, as applicable, for criteria pollutants non-methane hydrocarbons (NMHC), nitrogen oxides (NOx), carbon monoxide (CO), and particulate matter (PM), and for smoke opacity as demonstrated during the Acceleration (ACL) and Lugging (LUG) modes, and the peak value (PEAK) in either mode of the Smoke Opacity cycle, as set forth in 13 CCR 2423 and the applicable California test procedures for off-road compression-ignition engines, and 2) family emission limits (FEL) declared by the manufacturer as allowed by the applicable California test procedures, stated in units of gram per kilowatt-hour (g/kW-hr) and percent opacity (%opacity), respectively, except as noted, or designated as not applicable (\*).

Applicable Standard		Criteria				Smoke Opacity		
		NMHC	NOx	CO	PM	ACL	LUG	PEAK
Tier 4 Final 75 ≤ kW < 130	STD	0.19	0.40	5.0	0.02	*	*	*
	FEL	*	*	*	*	*	*	*
	NTE	0.28	0.60	6.2	0.03	*	*	*


**BE IT FURTHER RESOLVED:** Any declared FEL is the emission limit to which all engines must comply in lieu of the standard limit for certification purposes, subject to the restrictions of averaging, banking, or trading (ABT) programs allowed by the applicable California test procedures.

**BE IT FURTHER RESOLVED:** For the listed engine models, the manufacturer has submitted materials to demonstrate certification compliance with 13 CCR 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control warranty).

**BE IT FURTHER RESOLVED:** The listed engine models may only be installed in or on equipment such that engine operation is consistent with off-road compression-ignition engines as defined in 13 CCR 2421(a)(39).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this 27<sup>th</sup> day of September 2024.



Robin U. Lang, Chief  
 Emissions Certification and Compliance Division

**ATTACHMENT: ENGINE MODELS**

Family: SDZXL06.1059 EO Number: U-R-013-0753 Date Applicable: 9/9/2024

Model	Code	Trim	Config	Displacement	Peak Power			Peak Torque			ECS Num	GHG	Notes
					Power	Speed	Fueling	Torque	Speed	Fueling			
-	-	-	-	L	hp	rpm	lb/hr	lb-ft	rpm	lb/hr	-	-	-
TCD 6.1 L6	CFVI129		L6	6.057	172.9	2200	64.8	553.2	1450	52.4	1	N/A	
TCD 6.1 L6	C5VI105		L6	6.057	140.8	2000	50.9	464.7	1450	44.2	1	N/A	
TCD 6.1 L6	CFVI120		L6	6.057	160.9	1800	56.6	549.5	1450	52.1	1	N/A	
TCD 6.1 L6	CFVI129B		L6	6.057	172.9	2100	63.4	553.2	1450	52.4	1	N/A	
TCD 6.1 L6	C5VI129B		L6	6.057	172.9	2100	63.4	553.2	1450	52.4	1	N/A	
TCD 6.1 L6	C5VI129		L6	6.057	172.9	2200	64.8	553.2	1450	52.4	1	N/A	
TCD 6.1 L6	C5VI129C		L6	6.057	160.9	1800	56.6	553	1450	52.1	1	N/A	
TCD 6.1 L6	CFVI105		L6	6.057	140.8	2000	50.9	464.7	1450	44.2	1	N/A	
TCD 6.1 L6	CFVI129A		L6	6.057	172.9	2000	61.9	553.2	1450	52.4	1	N/A	
TCD 6.1 L6	C5VI129A		L6	6.057	172.9	2000	61.9	553.2	1450	52.4	1	N/A	
TCD 6.1 L6	CFVI129C		L6	6.057	160.9	1800	56.6	553	1450	52.1	1	N/A	